

Gas Hose - LPG Delivery - GHMB 375 D

Application/service:

Mandrel built hose for discharge service of liquid or gaseous LPG (propane and butane or any combination of these mixtures) and natural gas, either at room temperature or refrigerated, from tank trucks and wagons.



Construction:

Tube: black, smooth, synthetic rubber resistant to liquid gases, gasproof.

Reinforcement: synthetic cord plies and stainless steel antistatic wire.

Cover: black, smooth (cloth finish) synthetic rubber oil, fuel, lubricants and ageing resistant. It is pin-pricked.

Meets EN 1762:03 type D specifications.

Working temperature: -30°C to +45°C (-22F to +113°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		bending radius		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	m	ft
25	1	39	1.54	25	375	100	1500	0.90	0.60	200	7.9	61	200
32	1-1/4	47	1.85	25	375	100	1500	1.16	0.78	250	9.8	61	200
38	1-1/2	53	2.09	25	375	100	1500	1.35	0.91	300	11.8	61	200
51	2	67	2.64	25	375	100	1500	1.98	1.33	420	16.5	61	200
63.5	2-1/2	85	3.35	25	375	100	1500	3.31	2.22	500	19.7	61	200
76	3	97	3.82	25	375	100	1500	3.51	2.36	600	23.6	61	200
80	3-1/8	101	3.98	25	375	100	1500	3.63	2.44	650	26.6	61	200
102	4	126	4.96	25	375	100	1500	5.11	3.43	800	31.5	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.