

Hot Water Washdown - HW 150 D

Application/service:

For cold and hot water up to +100 C (+212 F) where steam is mixed with water. Used for washdown service in paper mill, food processing and handling plants. Also available with white rubber when a non marking cover is required. Food quality tube available on request.



Construction:

Tube: black, smooth, synthetic rubber, heat resistant.

Reinforcement: synthetic cord plies.

Cover: black, smooth (cloth finish) synthetic rubber wear, ageing, oil and fats resistant.

Working temperature: -40 C to +100 C (-40 F to +212 F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
13	1/2	23	0.91	10	150	30	450	0.33	0.22	61	200
16	5/8	26	1.02	10	150	30	450	0.38	0.26	61	200
19	3/4	29	1.14	10	150	30	450	0.51	0.34	61	200
25	1	35	1.38	10	150	30	450	0.60	0.40	61	200
32	1-1/4	43	1.69	10	150	30	450	0.85	0.57	61	200
38	1-1/2	52	2.05	10	150	30	450	1.20	0.81	61	200
51	2	66	2.60	10	150	30	450	1.73	1.16	61	200

Other sizes available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.