

# Material Handling - Sandblasting - MHSB 180 D

## Application/service:

For sand, corundum, grit, shot blasting work of metal castings, steel, stone, concrete surfaces and wherever abrasive materials are carried at high speed.



## Construction:

**Tube:** black, smooth high abrasion resistant rubber, static conductive.

**Reinforcement:** synthetic cord plies.

**Cover:** black, smooth (cloth finish) synthetic rubber ozone, weather and abrasion resistant. Static conductive.

**Working temperature:** -40°C to +70°C (-40°F to +158°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
13	1/2	25	1.00	12	180	36	540	0.44	0.30	61	200
19	3/4	33	1.30	12	180	36	540	0.65	0.44	61	200
25	1	40	1.57	12	180	36	540	0.87	0.58	61	200
32	1-1/4	48	1.89	12	180	36	540	1.16	0.78	61	200
38	1-1/2	54	2.13	12	180	36	540	1.41	0.95	61	200
51	2	71	2.80	12	180	36	540	2.15	1.44	61	200
63,5	2-1/2	83,5	3.29	12	180	36	540	2.58	1.73	61	200
76	3	96	3.78	12	180	36	540	3.43	2.30	61	200
102	4	126	4.96	12	180	36	540	5.55	3.73	61	200

Other dimensions and pressures available on request.

\* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.