

# Tank Truck - Dry Cement Delivery - TTDC 90 D

## Application/service:

Softwall hose for the pneumatic transfer of bulk cement and other dry bulk materials such as sand, gravel, silica and feed granules. Suitable for tank truck and silo discharge.



## Construction:

**Tube:** black, smooth, abrasion resistant rubber, antistatic.

**Reinforcement:** synthetic cord plies.

**Cover:** black, smooth (cloth finish) synthetic rubber weather, ozone and abrasion resistant. Antistatic.

**Working temperature:** -40°C to +70°C (-40°F to +158°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
76	3	94	3.70	6	90	18	270	2.68	1.80	61	200
90	3-35/64	106	4.17	6	90	18	270	2.95	1.96	61	200
102	4	118	4.65	6	90	18	270	3.20	2.15	61	200
127	5	145	5.71	6	90	18	270	4.12	2.77	61	200

Other dimensions and pressures available on request.

\* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.