

BLASTING HOLE LOADING - BHL 100 D

Application/service:

For explosive (including Ammonium Nitrate pellets) loading in blasting holes.



Construction:

Tube: black, smooth synthetic rubber abrasion resistant, static conductive.

Reinforcement: synthetic cord plies.

Cover: black, smooth (cloth finish) conductive synthetic rubber ozone, hydrocarbons and abrasion resistant.

Fire resistant cover to ISO 15540:1999 specs (+800°C / +1472°F for 30 minutes).

Working temperature: -30°C to +80°C (-22°F to +176°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
19	3/4	29	1.14	7	100	21	300	0.46	0.31	61	200
25	1	35	1.38	7	100	21	300	0.51	0.34	61	200
32	1-1/4	42	1.65	7	100	21	300	0.72	0.48	61	200
38	1-1/2	48	1.89	7	100	21	300	0.88	0.59	61	200
51	2	63	2.48	7	100	21	300	1.18	0.79	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.