

MINE CONDUIT - Cable Protection - M/MCCP

Application/service:

For use as an electric cable cover in underground mine service.



Construction:

Tube: black, smooth synthetic rubber static conductive.

Reinforcement: synthetic cord plies.

Cover: black, synthetic rubber ozone, and abrasion resistant, static conductive. Fire retardant.

Meets FRAS AS 1802 AS 2660 specifications.

Working temperature: -30°C to +80°C (-22°F to +176°F).

inside diameter		outside diameter		weight		Max. length*	
mm	inch	mm	inch	kg/m	lbs/ft	m	ft
13	1/2	21	0.83	0.25	0.17	61	200
16	5/8	24	0.94	0.30	0.20	61	200
19	3/4	29	1.14	0.42	0.28	61	200
25	1	35	1.38	0.52	0.35	61	200
32	1-1/4	42	1.65	0.65	0.44	61	200
38	1-1/2	48	1.89	0.75	0.50	61	200
45	1-3/4	55	2.17	0.88	0.59	61	200
51	2	61	2.40	1.00	0.67	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.