

OIL RIG - Drillwater 300 D

Application/service:

Used as a bulk hose in the offshore petroleum industry for the transfer of drilling water/fluid (mud) like freshwater, saltwater, lime, potassium and silicate from shore to supply vessels and from supply vessels to offshore platforms and drilling rigs. A tough, flexible, crush and kink resistant construction for long service life in the most arduous working conditions.



Construction:

Tube: black, smooth EPDM antistatic rubber abrasion, brine and sea water resistant.

Reinforcement: high tensile synthetic cord plies and antistatic copper wires.

Cover: black, smooth (cloth finish) CR rubber wear, oil, lubricants, heat and ageing resistant. Antistatic.

Fire resistant cover to ISO 15540:1999 specs (+800°C / +1472°F for 30 minutes).

Working temperature: -40°C to +100°C (-40°F to +212°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
51	2	68	2.68	20	300	80	1200	1.96	1.32	61	200
76	3	94	3.70	20	300	80	1200	3.30	2.22	61	200
102	4	122	4.80	20	300	80	1200	4.74	3.18	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.