

General Purpose Air/Water - GP 300 D

Application/service:

Air and water applications requiring maximum flexibility and kink resistance in construction, mining, agriculture, in-plant operations, oil rigs. Available on request with conductive tube and/or cover. A tough, flexible, kink resistant construction for long service life.



Construction:

Tube: black, smooth, synthetic rubber oil mist resistant.

Reinforcement: multiple layers of synthetic cord plies.

Cover: black, smooth (cloth finish) synthetic rubber oil mist, wear, weather and ozone resistant. Available on request in yellow, green or blue cover.

Working temperature: -30°C to +80°C (-22°F to +176°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
13	1/2	23	0.91	20	300	60	1200	0.40	0.27	61	200
16	5/8	26	1.02	20	300	60	1200	0.46	0.31	61	200
19	3/4	30	1.18	20	300	60	1200	0.58	0.39	61	200
25	1	37	1.46	20	300	60	1200	0.80	0.54	61	200
32	1-1/4	44	1.73	20	300	60	1200	1.11	0.75	61	200
38	1-1/2	53	2.05	20	300	60	1200	1.49	1.00	61	200
51	2	64	2.52	20	300	60	1200	1.56	1.05	61	200
63,5	2-1/2	79	3.11	20	300	60	1200	2.52	1.69	61	200
76	3	92	3.62	20	300	60	1200	2.89	1.94	61	200
102	4	118	4.65	20	300	60	1200	3.92	2.63	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.