Food & Beverage - Fatty Foods - FBFF 150 D

Application/service:

For delivery of vegetable oils and other edible oils, animal fat and also soybeans, mustard, salad dressings, vinegar and other acetic acid applications.

The hose can be sterilized with steam at +130 $^{\circ}$ C (+266 $^{\circ}$ F) for 30 minutes; rinse with potable water.



Construction:

Tube: white, smooth, special food quality synthetic rubber, taste-free and odourless. **Reinforcement:** synthetic cord plies.

Cover: blue, smooth (cloth finish) synthetic rubber resistant to oil and fat, wear, weather and ozone.

Meets FDA and European standards.

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
19	3/4	29	1.14	10	150	30	450	0.48	0.32	61	200
25	1	37	1.46	10	150	30	450	0.81	0.54	61	200
32	1-1/4	46	1.81	10	150	30	450	1.20	0.81	40	130
38	1-1/2	54	2.13	10	150	30	450	1.55	1.04	40	130
51	2	67	2.64	10	150	30	450	1.96	1.32	40	130
65	2-9/16	87	3.43	10	150	30	450	3.60	2.42	40	130
76	3	100	3.94	10	150	30	450	4.48	3.01	40	130
102	4	132	5.20	10	150	30	450	7.25	4.87	40	130


Working temperature: -30°C to +90°C (-22°F to +203°F).

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.



leamlec

Technical Catalogue - Edition 01/2013