

# Material Handling - Plaster Spraying - MHPS 600 D

## Application/service:

For the spraying at high pressure of wet plaster, concrete, gypsum and other abrasive materials, for use on both stationary and mobile systems.



## Construction:

**Tube:** black, smooth high abrasion resistant rubber, static conductive.

**Reinforcement:** synthetic cord plies.

**Cover:** black, smooth (cloth finish) synthetic rubber ozone, weather and abrasion resistant. Static conductive.

**Working temperature:** -40°C to +70°C (-40°F to +158°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
19	3/4	32	1-1/4	40	600	120	1800	0.53	0.36	61	200
25	1	37	1.46	40	600	120	1800	0.64	0.43	61	200
32	1-1/4	46	1.81	40	600	120	1800	0.88	0.59	61	200
38	1-1/2	54	2.13	40	600	120	1800	1.30	0.87	61	200
51	2	69	2.72	40	600	120	1800	1.96	1.32	61	200
63,5	2-1/2	83,5	3.29	40	600	120	1800	2.58	1.73	61	200
76	3	98	3.86	40	600	120	1800	3.45	2.32	61	200
102	4	130	5.12	40	600	120	1800	5.68	3.82	61	200

Other dimensions and pressures available on request.

\* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.