

Petroleum Products - Hot Bitumen - PPHB 150 SD

Application/service:

Hardwall hose construction for suction and delivery of hot bitumen and asphalt from tank truck, wagons, tankers.

For longer life clean and drain hose after use.



Construction:

Tube: black, smooth, synthetic rubber suitable for hot bitumen.

Reinforcement: synthetic cord plies and embedded steel wire helix.

Cover: black, smooth (cloth finish) synthetic rubber wear, oil, lubricants, bitumen, heat and ageing resistant.

Working temperature: -15°C to +185°C (-+5°F to +365°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		bending radius		vacuum	Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
51	2	68	2.68	10	150	40	600	2.55	1.71	280	11.0	0.9	61	200
63.5	2-1/2	78	3.07	10	150	40	600	2.90	1.95	350	13.8	0.9	61	200
76	3	94	3.70	10	150	40	600	3.72	2.50	450	17.7	0.9	61	200
102	4	124	4.88	10	150	40	600	5.71	3.84	650	25.6	0.9	61	200

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.