

Water Discharge - Lay Flat Construction - W 100 DLF

Application/service:

Water discharge in heavy duty service requiring a lightweight, compact hose, easy to handle. Suitable for industrial waters and waste water, it is used in agriculture, mining and industrial applications.



Construction:

Tube: black, smooth, synthetic rubber.

Reinforcement: synthetic cord plies.

Cover: black, smooth (cloth finish) synthetic rubber weathering and ozone resistant.

Working temperature: -30°C to +80°C (-22°F to +176°F).

inside diameter		outside diameter		working pressure		burst pressure		weight		Max. length*	
mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
51	2	57	2.24	10	150	30	450	0.64	0.43	61	200
63,5	2-1/2	70,5	2.78	10	150	30	450	0.91	0.61	61	200
76	3	83	3.27	10	150	30	450	1.10	0.74	61	200
102	4	109	4.29	8	120	24	360	1.39	0.93	61	200
127	5	134	5.28	7	105	22	330	1.64	1.10	61	200
152	6	160	6.30	10	150	30	450	2.48	1.67	61	200
203	8	213	8.39	8	120	24	360	3.98	2.67	18,3	60
254	10	265	10.43	7	105	21	315	5.70	3.83	18,3	60
305	12	318	12.52	7	105	21	315	7.45	5.01	18,3	60

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.