MINING - Air/Water LL GOLD LINE - M/AWGOL 255 D

Application/service:

Long length hose for underground mining and industrial air, water and oil-mist water pressure service.



Construction:

Tube: black, smooth synthetic rubber, oil mist resistant.
Reinforcement: high tensile synthetic braid.
Cover: black, smooth synthetic rubber wear, oil mist, heat and ageing resistant.
Marking: yellow continuous stripe.

Generally in accordance to SABS 988 HD specifications.

| Working temperature: - | -25°C to +80°C | (-13°F to +176°F). |
|------------------------|----------------|--------------------|
|------------------------|----------------|--------------------|

| inside d | inside diameter | | outside diameter | | working pressure | | burst pressure | | weight | | Max. length* | |
|----------|-----------------|----|------------------|-----|------------------|-----|----------------|------|--------|-----|--------------|--|
| mm | inch | mm | inch | bar | psi | bar | psi | kg/m | lbs/ft | m | ft | |
| 13 | 1/2 | 23 | 0.91 | 17 | 255 | 68 | 1020 | 0.40 | 0.27 | 100 | 330 | |
| 19 | 3/4 | 29 | 1.14 | 17 | 255 | 68 | 1020 | 0.55 | 0.37 | 100 | 330 | |
| 25 | 1 | 37 | 1.46 | 17 | 255 | 68 | 1020 | 0.91 | 0.61 | 100 | 300 | |

Other dimensions and pressures available on request.

* All lengths coiled and wrapped in polyethylene film.

leamlec

Specific cut lengths available. Please, contact Customer Service for details.

Due to a continual improvement of the products, we reserve the right to alter the hose specifications without prior notice.

Progressing together

Mine Catalogue - Edition 01/2013